



You're safe with....

EVERSAFE



Fire Extinguisher Cabinets

Fire Extinguishers installed in aggressive environments such as where there is a high level of moisture, dust laden, corrosive areas or direct UV exposure should be pressure tested and refilled every THREE years instead of every five years according to the requirements of Australian Standard AS 1851. Save on your maintenance costs by installing the equipment in a cabinet.



'DOME LID' FIRE EXTINGUISHER CABINETS:

DOME LID CABINETS ARE PARTICULARLY IDEAL FOR INSTALLATION IN MOISTURE AND DUST LADEN AREAS AND ALSO HIGH TRAFFIC AREAS SUCH AS RAIL OR BUS STATIONS.

- UV RESISTANT MATERIAL
- NO SHARP EDGES.
- QUICK ACCESS
- AVAILABLE IN A RANGE OF SIZES TO SUIT ANY EXTINGUISHER

PRODUCT CODES:

- PDL – 3:** Suits 2.5kg to 4.5kg Extinguishers
PDL – 1: Suits 6.0kg to 9.0kg Extinguishers
PDL – 2: Suits 5.0kg CO2 Extinguishers

'CATO' FIRE EXTINGUISHER CABINETS:

INJECTION MOULDED LOCKING CABINETS ARE IDEAL FOR INSTALLATION IN AREAS WHERE THEFT OR VANDALISM IS A RISK.

- EASY BREAK PANEL ACCESS IN AN EMERGENCY
- FIRE SERVICE '003' KEY LOCK.
- UV RESISTANCE
- ECONOMICAL EQUIPMENT 'SECURITY'

PRODUCT CODES

- CENLS:** Suits 1.0kg to 2.0kg Extinguishers
CENLM: Suits 2.5kg to 4.5kg Extinguishers
CENLL: Suits 4.5kg to 9.0kg Extinguishers

